

## Transparent Refill Friendly HP #02 Cartridges

The MIS Transparent Refill Friendly HP #02 cartridges use a check valve system to prevent ink from draining out of the exit port, as well as control incoming air. Original HP carts use a bag and **cannot** be refilled using this method.



Transparent Refill Friendly HP #02 Black Cartridge

1. Set the cartridge that you are going to fill on a flat surface like a tabletop or work bench. It is important to cover the surface with newspaper or plastic to protect against spills.



2. Remove the safety cap from the end of a syringe and install a 1½" long needle. It is a twist lock connection.



3. Carefully load the syringe with ink following the table below for each color

Color Position	Capacity
Cyan	12ml
Magenta	12ml
Yellow	12ml
Light Magenta	12ml
Light Cyan	12ml
Black	30ml

Dip the needle into the bottle of ink and pull back on the syringe. Make sure it is the right color for the cartridge you are filling.



4. Remove the fill plug from the top of the cartridge. The fill plug is black in the picture

## Transparent Refill Friendly HP #02 Cartridges

of the cartridge on the previous page.

5. Carefully insert the needle into the fill hole on top of the cartridge and slowly inject the ink until the cartridge is full (as indicated by a  $\frac{1}{4}$ " air gap at the top of the cartridge), or until the syringe is empty.

With **new cartridges** please use the fill chart above. As cartridges can be **refilled before being entirely depleted**, used cartridges will require different amounts of ink depending on their state of depletion.



6. Once the cartridge has been filled, replace the fill plug and install the cartridge into the printer.



7. **Note:** these cartridges will report full in your ink monitor if they are removed and reinstalled without being refilled.